

MULTI DOOR CAMERA DRC-nUC



FEATURES

- DRC-7UC
- 7 button wide name plate
- Built-in illumination sensor
- Flush-mounted type
- House call and talk

FEATURES

- DRC-6UC
- 6 button wide name plate
- Built-in illumination sensor
- Flush-mounted type
- House call and talk

FEATURES

- DRC-5UC
- 5 button wide name plate
- Built-in illumination sensor
- Flush-mounted type
- House call and talk

FEATURES

- DRC-4UC
- 4 button wide name plate
- Built-in illumination sensor
- Flush-mounted type
- House call and talk

FEATURES

- DRC-3UC
- 3 button wide name plate
- Built-in illumination sensor
- Flush-mounted type
- House call and talk

FEATURES

- DRC-2UC
- 2 button wide name plate
- Built-in illumination sensor
- Flush-mounted type
- House call and talk

SPECIFICATION

Power source	DC12V/1A
Image sensor	Color C-MOS
Min. illumination	0.1Lux(up to 300mm)
Wiring	4-wire with polarity
Operating temp.	-10°C~+50°C
Lighting	Built-in white LED(3pie) 2 EA

Camera view angle	Horizontal: 75°, Vertical: 55°
Camera angle adjusting	Ascendant 13°, Descendant 13°
Scanning frequency	NTSC / PAL
Distance	ø0.5 : 28m/ø0.65 : 50m
Dimension(mm)	130(W)×315(H)×10(D)

